



General Purpose Corded Handheld Laser Bar Code Reader

The QuickScan reader series is Datalogic Scanning's value line of general purpose handheld data collection products. The QuickScan QS6000 Plus laser scanner offer premium performance in a value priced general purpose product. An ideal solution for retail, healthcare, office automation and light industrial applications, the QS6000 Plus products offer an excellent depth-of-field, with reading out to 95.0 cm / 37.4 in on 55 mil labels and with 100% UPC codes, it reads from an impressive 33.0 cm / 13.0 in.

A bright, well-defined scan line allows the targeting and reading of codes even in bright light conditions. Its advanced optics perform well even when reading low contrast labels with poor edge definition.

Dual interfaces allow the QS6000 Plus reader to be very flexible; switching interfaces is as easy as changing cables. Featuring an IP53 sealing rating the QS6000 Plus has a strong, plastic enclosure that guards against liquid and dust infiltration. A tough, rubber like over mold cushions the scanner when dropped, protects the scan

window and prevents the scanner from slipping off counter surfaces. Anti-shock mounts additionally protect the internal engine and optics.

A hands-free AutoSense® stand for presentation style reading and mounting options are available to organize the workspace and to save valuable counter area when needed.



Features

- Excellent depth of field
- Universal Wedge for additional keyboard emulation, symbology support and data editing
- Supports GS1 DataBar™ linear codes (select models)
- Water and Particulate Sealing Rating: IP53
- Drop resistance to 1.5 m / 4.9 ft



Specifications

DECODING CAPABILITY

1D / LINEAR CODES
Autodiscriminates all standard 1D codes including GS1 Databar™ linear codes

ELECTRICAL

CURRENT
Operating (Typical): 130 mA @ 5 VDC
Standby/Idle (Typical): 35 mA @ 5 VDC

INPUT VOLTAGE
4.5 - 14 VDC

ENVIRONMENTAL

AMBIENT LIGHT
12,900 lux

DROP RESISTANCE
Withstands repeated drops from 1.5 m / 4.9 ft onto a concrete surface

ESD PROTECTION (AIR DISCHARGE)
25 kV

HUMIDITY (NON-CONDENSING)
5 - 95%

PARTICULATE AND WATER SEALING
IP53

TEMPERATURE
Operating: 0 to 50 °C / 32 to 122 °F
Storage/Transport: -40 to 70 °C / -40 to 158 °F

INTERFACES

IBM 46xx; Keyboard Wedge; RS-232; Universal Keyboard Wedge;
Universal USB; USB; Single and Dual Interfaces Available

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE
Black; Grey

DIMENSIONS
16.5 x 7.1 x 10.7 cm / 6.5 x 2.8 x 4.2 in

WEIGHT
204.0 g / 7.2 oz

READING PERFORMANCE

LIGHT SOURCE
650 nm VLD

PRINT CONTRAST RATIO (MINIMUM)
30%

READ RATE (MAXIMUM)
35 reads/sec.

READING ANGLE
Pitch: +/- 65°; Roll (Tilt): +/- 30°; Skew (Yaw): +/- 55°

READING INDICATORS
Beeper (Adjustable Tone); Good Read LED

RESOLUTION (MAXIMUM)
0.130 mm / 5 mils

READING RANGES

TYPICAL DEPTH OF FIELD
Minimum distance determined by symbol length and scan angle.
Printing resolution, contrast, and ambient light dependent.

5 mils: 7.0 to 18.0 cm / 2.7 to 7.0 in
7.5 mils: 6.0 to 28.0 cm / 2.3 to 11.2 in
10 mils: 4.5 to 40.0 cm / 1.8 to 15.6 in
13 mils: 5.1 to 56.0 cm / 2.0 to 22.0 in
20 mils: 5.1 to 76.0 cm / 2.0 to 30.0 in

SAFETY & REGULATORY

AGENCY APPROVALS
The product meets necessary safety and regulatory approvals for its intended use.
The Quick Reference Guide for this product can be referred to for a complete list of certifications.

ENVIRONMENTAL COMPLIANCE
Complies to China RoHS

LASER CLASSIFICATION
Caution Laser Radiation - Do not stare into beam; CDRH Class II; IEC 60825 Class 2

UTILITIES

OPOS / JAVAPOS
JavaPOS Utilities are available for download at no charge
OPOS Utilities are available for download at no charge

WARRANTY

5-Year Factory Warranty



Cases/Holsters

- 5-0788 Universal Holster



Mounts/Stands

- 7-0204 Stand, AutoSense
- 7-0393 Mount, Tabletop
- 7-0470 Stand, AutoSense, No Base

© 1998-2009 Datalogic Scanning Inc.

All rights reserved. • Protected to the fullest extent under U.S. and international laws.
• Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic is a registered trademark of Datalogic S.p.A. In many countries and the Datalogic logo is a trademark of Datalogic S.p.A. • QuickScan and AutoSense are registered trademarks of Datalogic Scanning Inc.

Other brand and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

DS-QUICKSCANQS6000PLUS-ENA4 20090716

www.scanning.datalogic.com